

Reli-A-Pak® Bolt, Nut, & Gasket Sets by Reliable Fasteners, Inc.

PRODUCT INFO

BILTRITE

Neoprene Blended Sheet

Style 10 Smooth Finish

Style	Thickness		Durometer Hardness Shore A ±5	Tensile	Elongation	Temperature	Wt. Per		Specifications
	Inches	Width Inches					Lin. Foot 36"	Finish	
10	1/16 thru 1	36 & 48	40	800	350	-20°F to +170°F	1/8-2.5	Smooth	ASTM D-2000 SAE J200, 1BC 408Z1* MIL R-3065, SC 408Z1*
10	1/16 thru 2	36 & 48	50	800	300	-20°F to +170°F	1/8-2.6	Smooth	ASTM D-2000 SAE J200, 1BC 508 MIL R-3065, SC 508
10	1/32 thru 2 1/16, 1/8, 1/4	36 & 48 72	60	900	300	-20°F to +170°F	1/8-2.7	Smooth	ASTM D-2000 SAE J200, 1BC 609 MIL R-3065, SC 609
10	1/16 thru 2	36 & 48	70	1000	200	-20°F to +170°F	1/8-2.7	Smooth	ASTM D-2000 SAE J200, 1BC 710 MIL R-3065, SC 710
10	1/16 thru 2	36 & 48	80	1000	100	-20°F to +170°F	1/8-2.9	Smooth	ASTM D-2000 SAE J-200, 1BC 810 MIL R-3065, SC 810

* Z1 Elongation 350%